



DIMENSIONS														
FLANGE						COUPLING								
SAE J617	N	P	Z	NR	a	SAE J620	PA	MA	Y	NR	φ	b	WA	WB
5	314.32	360	8	11.5	45°	6 1/2	215.9	200	6	9	60°	30.2	13	
4	361.95	407	12	11.5	30°	7 1/2	241.3	222.3	8	9	45°	30.2	13	
3	409.58	455	12	11.5	30°	8	263.52	244.48	6	11	60°	62	-	
						10	314.3	295.3	8	11	45°	53.8	13	
						11 1/2	352.4	333.4	8	11	45°	39.6	13	

SUPPORT BEARINGS	PROTECTION DEGREE	TYPE OF CONSTRUCTION IM	DIMENSIONS
ROLLING	IP23	B2	mm

CONNECTINGS			
COUPLING	FLANGE SAE J617		
SAE J620	5	4	3
6 1/2	X		
7 1/2	X	O	
8	X	X	X
10		X	X
11 1/2			X

X AVAILABLE
O MOST COMMON

TYPE	DIMENSIONS		
	L	F	CG SAE 3-4-5
XA	416	200	198
SA			202
MX			208
MA			210
LA			223

= FIRST ISSUE		D.Pegoraro			
REV	DESCRIPTION	PREPD	CHKD	APPRD	DATE
ECCO:	HEAT TREATMENT:	MAT:		IND. ENG. CHKD:	
JOB:	SURFACE TREATMENT:	RAW MAT. CODE:			
MarelliMotori Inspired solutions		DIMENSIONS WITHOUT TOLERANCES PRECISION DEGREE: (TN F 3661)		DIMENSION: mm SCALE: 1:4 WEIGHT (kg): n/a	
OVERALL DIMENSIONS MXB-E 160 B2 SYNCHRONOUS GENERATOR				M16AD025B	
This document is the property of Marelli Motori S.p.A. No part of this document may be copied or reproduced in any way. This information is subject to constant review. Measurements on printed drawing are not allowed, any missed dimension or information on the drawing must be pointed out to MarelliMotori.					