



TYPE	DIMENSIONS			
	L	F	CG SAE4-SAE3	CG SAE2-SAE1
XA 4	708	325	325	312
XB 4			329	317
SB 4			352	348
MA 4	778	375	344	331
MB 4			386	372
LA 4			389	377
LB 4	843		436	423

SUPPORT BEARINGS	PROTECTION DEGREE	TYPE OF CONSTRUCTION IM	DIMENSIONS
ROLLING	IP23	B2	mm

DIMENSIONS														
FLANGE						COUPLING								
SAE	N	P	M	Z			SAE J620	PA	MA	Y			WA	WB
				No	DIA	a				No	DIA	b		
4	361.95	460	381.00	12	11	30°	10	314.32	295.28	8	11	45°	53.8	/
3	409.58	460	428.62	12	11	30°	11 1/2	352.42	333.38	8	11	45°	39.6	/
2	447.68	495	466.72	12	11	30°	14	466.72	438.15	8	14	45°	25.4	14
1	511.18	552.5	530.22	12	11	30°								

CONNECTINGS						
COUPLING	FLANGE					
	SAE J 617					
SAE J620	4	3	2	1		
10	X	X				
11 1/2		O	X	X		
14				X		
MOST COMMON		O				

FIRST ISSUE		D. Pignato			
REV	DESCRIPTION	PREP'D	CHK'D	APPR'D	DATE
ECCO:	HEAT TREATMENT:	WAT:	IND. ENG. CHK'D:		
JOB:	SURFACE TREATMENT:	RAW MAT CODE:			
DIMENSIONS WITHOUT TOLERANCES PRECISION DEGREE: (IN F 3661)		DIMENSION: mm		WEIGHT (kg)	ATEX APPR'D:
MarelliMotori Inspired solutions		A2		SCALE: 1:3	n/a
OVERALL DIMENSIONS MXB-E 225 SYNCHRONOUS GENERATOR				M22AD210C	
This document is the property of Marelli Motor S.p.A. No part of this document may be copied or reproduced in any way. This information is subject to constant review. Measurements on printed drawing are not allowed, any missed dimension or information on the drawing must be pointed out to Marelli Motor.					SHEET: 1 OF: 1